



## VTA SERIES VAPOR TIGHT LINEAR

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

ABS material housing, compact design with semi-gloss White finish. 3/4" knockout back and end of housing for end mount sensor, through wiring or surface conduit mount.

### OPTICS

End-to-end diffused polycarbonate (PC) lens.

### ELECTRICAL

Delivered average 135lm/W efficacy LEDs offer 80+ color rendering index (CRI).  
Field Selectable Output and CCT (see ordering information for detail).  
L70 >100,000 hours expected life.  
-40°C up to 45°C (-40°F up to 113°F) maximum operating temperature.  
Driver operates at 120-277V input, 0-10V dimmable driver, down to 10%.

### MOUNTING

Designed for direct wire or as a portable luminaire with use of power cord.\*  
Standard surface mountable underneath electrical box, or surface conduit mount through 3/4" knockout.

### FINISH

Semi-gloss White finish standard, IP66 for wet location.

### CERTIFICATION

IP66 Wet location label standard.  
All luminaires are built to UL1598 standards and bear appropriate cULus labels.  
For Emergency application, equipment with [UL924](#) certified battery packs.  
DLC® (DesignLights Consortium) listed.

### WARRANTY

5 year warranty, see Limited Warranty for additional information.



### Shipping Data

Product	Measurement	Weight
VTA-30	27"L x 6"W x 4"H	4 lb
VTA-45	52"L x 6"W x 4"H	6 lb
VTA-90	96"L x 6"W x 4"H	12 lb





## VTA SERIES VAPOR TIGHT LINEAR

Order Information					Example : VTA 45 SC WH UD	
Fixture	Series	Power & LM	CCT	Finish	Input	
	VTA			WH	UD	
Accessories Options						

### A Series

VTA Vapor Tight Linear Field Selectable Output & CCT

### B Power & LM

Code	Size	Power	LM
30	2-Foot	Field Selectable 20/25/30W	2872 ~ 4021
45	4-Foot	Field Selectable 34/38/45W	4941 ~ 6494
90	8-Foot	Field Selectable 65/75/90W	9295 ~ 12364

### C CCT

SC Field Selectable 3500K / 4000K / 5000K

### D Finish

WH White

### E Input

UD 120-277V, 0-10V Dimmable

### F Accessories/Options

AIA	Assembled in America, compliant with BAA (COTS)
MOUNT-VT-HOOK	V Hook Mount - chain provided by others
EMB-EMS8W27	Integral 8W Self-Diagnostic Emergency Battery, Operating Temp: 0C ~ 50C
EMB-EMS15W27	Integral 15W Self-Diagnostic Emergency Battery, Operating Temp: 0C ~ 50C
EMB-EMS20W27	Integral 20W Self-Diagnostic Emergency Battery, Operating Temp: 0C ~ 50C
SENSOR-819-O2*	End mount on/off motion sensor highbay lens (120-277V)
SENSOR-819-D2*	End mount on/off/dimming and photocell sensor highbay lens (120-277V, 1-10V Dimming)
SENSOR-LSXR-10-ADC*	End mount on/off/dimming daylight harvesting sensor lowbay lens (120-277V, 0-10V Dimming)
SURGE-LSP4-U	10kV Surge Protector (110-277V)
-PLUG	6-Foot Black cord and plug (3-prong)
-CORD	18-3 300V 6 Foot Cord
TWIST-LOCK	Specify Plug Type: L515P / L715P / HBL5929 / L8-20P

## VTA SERIES VAPOR TIGHT LINEAR

### Dimensions

Model	L	W	H
VTA-30	24.80" (630mm)	5.00" (127mm)	3.50" (88.5mm)
VTA-45	49.80" (1265mm)	5.00" (127mm)	3.50" (88.5mm)
VTA-90	94.50" (2400mm)	5.00" (127mm)	3.50" (88.5mm)

