



ES-EDGE SERIES LED EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Extruded aluminum mounting canopy.

OPTICS

Constructed of clear acrylic. Stencil letters are 6" high with 3/4" stroke, with minimum of 100 ft. viewing distance rating as required by UL 924 standard. Double face panels are supplied with a mirror insert. High output red or green LEDs provide superior brightness. Energy consumption of less than 3W for AC only and less than 5W for battery back-up units. LEDs are a maintenance-free solution, providing up to 100,000 hours of use without failure.

ELECTRICAL

Dual-voltage input 120 or 277VAC at 60Hz.
NiCad batteries are maintenance-free with a life expectancy of 15 years.
NiCad batteries offer high discharge rates and continue to perform in a vast temperature range from 32°F to 104°F (0°C to 40°C).
Optional: Self-Diagnostic Battery

MOUNTING

Surface Mounting: Universal mounting canopy for top or end ceiling mounting.
Mounting canopy, installation instructions & hardware (inside unit).

STANDARD FINISH

Brushed Aluminum.

CUSTOM FINISH

Black, White Finish.

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cULus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

SHIPPING DATA

Product	Measurement	Weight
ES-EDGE	14"L x 10"W x 3"H	4 lb



ES-EDGE SERIES LED EXIT SIGN

ORDER INFORMATION				EXAMPLE: ES-EDGE R BA EM
Fixture	Series	"EXIT" Color	Finish	Input
	ES-EDGE			EM
A SERIES				
ES-EDGE	Edgelit LED Exit Sign			
B "EXIT" COLOR				
Code	Color			
G	Green			
R	Red			
C FINISH				
Standard				
BA	Brushed Aluminum			
Optional Color				
CC	BK	Black	WH	White
D INPUT				
EM-S	90 Minute Self-Diagnostic Battery			

ES-EDGE SERIES LED EXIT SIGN

DIMENSIONS

Series	L	H	D
ES-EDGE	13.00" (330.20mm)	9.63" (244.60mm)	2.09" (53mm)

