



ES SERIES LED EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Sturdy thermoplastic, injection molded, V-0 flame retardant, high impact resistant housing.

OPTICS

Two "EXIT" Faceplates (with optional knockout arrows) and one blank faceplate included.

Color-matched diffuser eliminates hot spots and striations, providing optimal light output.

ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Easy to install. Universal mounting canopy for top or side installation. Mounting canopy, installation instructions & hardware (inside unit).

STANDARD FINISH

Corrosion resistant White finish.

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cETLus labels. All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

SHIPPING DATA

Product	Measurement	Weight
ES	12"L x 9"W x 3"H	3 lb



ES SERIES LED EXIT SIGN

ORDER INFORMATION		EXAMPLE: ES R WH EM		
Fixture	Series	“EXIT” Color	Finish	Input
	ES		WH	EM
A SERIES				
ES	LED Exit Sign			
B “EXIT” COLOR				
Code	Color			
G	Green			
R	Red			
C FINISH				
WH	White			
D INPUT				
EM	90 Minute Battery			

ES SERIES LED EXIT SIGN

DIMENSIONS

Series	L	W	D
ES	12.01" (305mm)	7.99" (203mm)	2.09" (53mm)

