



## CONTRACTOR SERIES WALL PACK

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Cast aluminum frame holds lens and seals to housing gasket with two stainless steel screws. Housing is completely sealed against moisture and environmental contaminants. Heat dissipating fins provide superior thermal performance extending the life of the luminaire.

### OPTICS

Full polycarbonate UV resistant front lens provides uniform distribution and glare control. CCT selectable between 3000K ~ 5000K (80 CRI) configuration settings.



### ELECTRICAL

80+ CRI Lumileds LED.  
-40°C up to 40°C (-40°F up to 104°F) maximum operating temperature.  
50,000hr LED at L70 @ 25°C.  
Available with CCT / Output Selectable Function.  
CSW-90 model output selectable 30W / 50W / 70W / 90W.  
CSW-120 model output selectable 50W / 80W / 100W / 120W.  
Universal Input 120-277V, 0-10V dimming with 12V AUX output.  
50/60Hz, <20% THD, 0.9 power factor.  
Built-In Photocontrol as standard.  
Optional 10kV Surge Protection.

### MOUNTING

Wall mount over electrical box or via surface conduit.

### STANDARD FINISH

Corrosion resistant Dark Bronze powder coating finish.

### CERTIFICATION

Wet Location listed.  
All luminaires are built to UL1598 standards and bear appropriate cULus labels.  
For Emergency application, equipped with UL924 certified battery packs.  
DLC® Premium (DesignLights Consortium Qualified) listed.

### WARRANTY

5 year warranty, see Limited Warranty for additional information.



**CONTRACTOR SERIES WALL PACK**

ORDER INFORMATION					EXAMPLE: CSW 90 SC DB UD-P
Fixture	Series	Power & LM	CCT	Finish	Input
	<b>CSW</b>		<b>SC</b>	<b>DB</b>	<b>UD-P</b>
Accessories					
Options					

**A SERIES**

CSW Contractor Series - Wall Pack

**B POWER & LM**

Code	Power	LM
90	Field Selectable 30W / 50W / 70W / 90W	4,800lm ~ 12,500lm
120	Field Selectable 50W / 80W / 100W / 120W	8,000lm ~ 16,500lm

**C CCT**

SC Field Selectable CCT 3000K / 4000K / 5000K

**D FINISH**

DB Dark Bronze

**E INPUT**

UD-P 120-277V, 0-10 Dimming with Built-in Photocell

**F ACCESSORIES/OPTIONS**

**SURGE-LSP4-U** 10kV Inline Surge Protection for Universal Input / **U:** 120-277V  
**EMB-8W-B\*\*** High Voltage Output Smart Emergency Battery 8W 100-347VAC Input 170VDC

\*\*see page 4 for emb spec

**CONTRACTOR SERIES WALL PACK**

**DIMENSIONS**

Model	H	L	D
CSW-90	9.25" (235mm)	14.20" (361mm)	4.43" (112mm)
CSW-120	9.70" (248mm)	17.99" (457mm)	4.5" (114mm)



